




Lamina^{INC} Heavy Duty Lami-Flex Springs



HEAVY DUTY (CONT.)

OUTSIDE DIA. (O.D.)	FITS PUNCH SHANK (A)	LENGTH (L)	CATALOG NUMBER	LOAD LBS. REQD. TO DEFLECT 1/8"	LOAD POUNDS REQUIRED TO DEFLECT									
					5%		10%		15%		20%		25%	
					LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.
2-1/4	1	1-1/4	L FH22510-125	2050		.0625		.1250		.1875				
		1-1/2	L FH22510-150	1955		.0750		.1500		.2250				
		1-3/4	L FH22510-175	1670		.0875		.1750		.2625				
		2	L FH22510-200	1600		.1000		.2000		.3000				
		2-1/4	L FH22510-225	1530	1470	.1125	2050	.2250	2580	.3375	N.R.		N.R.	
		2-1/2	L FH22510-250	1470		.1250		.2500		.3750				
		2-3/4	L FH22510-275	1410		.1375		.2750		.4125				
		3	L FH22510-300	1360		.1500		.3000		.4500				
		4	L FH22510-400	1315		.2000		.4000		.6000				
		25	L FH22510-2500											
2-3/4	1-1/2	1-1/4	L FH27515-125	2680		.0625		.1250		.1875				
		1-1/2	L FH27515-150	2550		.0750		.1500		.2250				
		1-3/4	L FH27515-175	2185		.0875		.1750		.2625				
		2	L FH27515-200	2125		.1000		.2000		.3000				
		2-1/4	L FH27515-225	2000		.1125		.2250		.3375				
		2-1/2	L FH27515-250	1920	1920	.1250	2680	.2500	3365	.3750	N.R.		N.R.	
		2-3/4	L FH27515-275	1790		.1375		.2750		.4125				
		3	L FH27515-300	1585		.1500		.3000		.4500				
		4	L FH27515-400	1435		.2000		.4000		.6000				
		25	L FH27515-2500											

EXTRA HEAVY DUTY Lami-Flex Springs

OUTSIDE DIA. (O.D.)	FITS PUNCH SHANK (A)	LENGTH (L)	CATALOG NUMBER	LOAD LBS. REQD. TO DEFLECT 1/8"	LOAD POUNDS REQUIRED TO DEFLECT									
					5%		10%		15%		20%		25%	
					LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.	LOAD LBS.	LENGTH OF DEFL.
1-1/2	5/8	1	L FX15063-100	1220		.0600		.1000		.1500		.2000		.2500
		1-1/4	L FX15063-125	1085		.0625		.1250		.1875		.2500		.3125
		1-1/2	L FX15063-150	990		.0750		.1500		.2250		.3000		.3750
		1-3/4	L FX15063-175	905	780	.0875	1083	.1750	1360	.2625	1620	.3500	1755	.4375
		2	L FX15063-200	865		.1000		.2000		.3000		.4000		.5000
		2-1/4	L FX15063-225	815		.1125		.2250		.3375		.4500		.5625
		2-1/2	L FX15063-250	780		.1250		.2500		.3750		.5000		.6250
		25	L FX15063-2500											
2	7/8	1-1/4	L FX20088-125	1640		.0625		.1250		.1875				
		1-1/2	L FX20088-150	1495		.0750		.1500		.2250				
		1-3/4	L FX20088-175	1365		.0875		.1750		.2625				
		2	L FX20088-200	1305		.1000		.2000		.3000				
		2-1/4	L FX20088-225	1225	1175	.1125	1640	.2250	2055	.3375	N.R.		N.R.	
		2-1/2	L FX20088-250	1175		.1250		.2500		.3750				
		2-3/4	L FX20088-275	1075		.1375		.2750		.4125				
		3	L FX20088-300	975		.1500		.3000		.4500				
25	L FX20088-2500													
2-1/2	1	1-1/4	L FX25010-125	3765		.0625		.1250		.1875				
		1-1/2	L FX25010-150	3445		.0750		.1500		.2250				
		1-3/4	L FX25010-175	2950		.0875		.1750		.2625				
		2	L FX25010-200	2780		.1000		.2000		.3000				
		2-1/4	L FX25010-225	2610	2445	.1125	3765	.2250	4875	.3375	N.R.		N.R.	
		2-1/2	L FX25010-250	2445		.1250		.2500		.3750				
		2-3/4	L FX25010-275	2345		.1375		.2750		.4125				
		3	L FX25010-300	2265		.1500		.3000		.4500				
4	L FX25010-400			.2000		.4000		.6000						
25	L FX25010-2500													