



# Unbrako



FLAT HEAD SOCKET CAP SCREWS							
diameter	length	UNRC-coarse			UNRF-fine		
		plain		with LOC-WEL	plain		with LOC-WEL
		alloy	stainless	alloy	alloy	stainless	alloy
#2 .050" Key	3/16						
	1/4						
	3/8						
	1/2						
#3 1/16" Key	1/4						
	3/8						
	1/2						
#4 1/16" Key	1/4						
	3/8						
	1/2						
	5/8						
#5 5/64" Key	1/4						
	3/8						
	1/2						
	5/8						
#6 5/64" Key	1/4						
	3/8						
	1/2						
	5/8						
#8 3/32" Key	1/4						
	3/8						
	1/2						
	5/8						
#10 1/8" Key	3/8						
	1/2						
	5/8						
	3/4						
1/4 5/32" Key	1						
	1-1/4						
	1-1/2						
	3/8						
	1/2						
	5/8						
3/4	1						
	1-1/4						
	1-1/2						
	1-3/4						
	2						
	2						

FLAT HEAD SOCKET CAP SCREWS (Cont'd)							
diameter	length	UNRC-coarse			UNRF-fine		
		plain		with LOC-WEL	plain		with LOC-WEL
		alloy	stainless	alloy	alloy	stainless	alloy
5/16 3/16" Key	1/2						
	5/8						
	3/4						
	1						
	1-1/4						
	1-1/2						
	1-3/4						
	2						
	2-1/4						
	1-1/2						
3/8 7/32 Key	1/2						
	5/8						
	3/4						
	1						
	1-1/4						
	1-1/2						
	1-3/4						
	2						
7/16 1/4" Key	3/4						
	1						
	1-1/4						
	1-1/2						
	1-3/4						
	2						
1/2 5/16" Key	3/4						
	1						
	1-1/4						
	1-1/2						
	1-3/4						
	2						
5/8 3/8" Key	1-1/4						
	1-1/2						
	1-3/4						
	2						
	2-1/4						
	2-1/2						
3/4 1/2" Key	1-1/4						
	1-1/2						
	1-3/4						
	2						
	2-1/4						
	2-1/2						

NOTES: Above items are also manufactured in shorter, longer and intermediate lengths- subject to special order requirements

 Indicates stock sizes available.